

**REF: 60934 REF****UK: 60942 REF****USA: 60938**

USE

- The QUAKE CAS ENERGY electric tile vibrator is a lightweight and compact tile vibrator, specially designed to prevent the generation of encapsulated air bubbles between the adhesive and the back of the ceramic tile, thus facilitating an ideal adhesion between adhesive and tile.
- The low weight and wireless system facilitate its use in vertical supports and work at height.

FUNCTIONAL CHARACTERISTICS

- For cementitious adhesives, resins and other materials.
- The new battery of the METABO CAS platform has LED indicators that indicate to the user the remaining charge level. If 4 green LEDs light up, the battery is at 80% capacity.
- The double bi-material handle offers greater ergonomics and comfort to the user, and its geometry facilitates better control and stability of the tool during vibration.
- The contact base with the ceramic tile leaves no marks and is easily replaceable.
- It has an on/off switch and a progressive push button for RPM control.



TECHNICAL SPECIFICATIONS

- Maximum load capacity: 50 kg.
- Suction cup diameter: Ø 127 mm.
- More than an hour of continuous work.
- Dimensions: 40x28.5x14 cm
- Weight: 3.6 kg
- Battery:
 - o Type: LI-HD CAS 18V 2Ah.
 - o Battery level indicator: by push button with 4 color LEDs.
 - o IP battery: 20
 - o Battery weight: 0.429 Kg
 - o Voltage: DC 18V
 - o Vibration frequency: 0 – 10,000 RPM
 - o Charging time: 2 hours

PACKAGING

- Cardboard groupage box with flexography at 1 ink.
- Box dime
- nsions: 42x30x30 cm
- Box weight: 8.1 kg
- Units in the box: 2

STANDARDS:

- Directives: 2006/42/EC, 2014/30/EU, 2011/65/EU, 2012/19/EU
- Standards: EN 62841-1:2015 EN 62841-2-10:2017, EN 55014-1:2017, EN 55014-2:2015.