

CONSTRUCTION Tufting 1/10" cut pile COC
STRUCTURE Tufté 1/10" velours COC
STRUKTUR Getuftet 1/10" COC-Velours
STRUCTUUR Getuft 1/10" velours COC

STAIR SUITABILITY EN 1963
ESCALIERS A: intensive use
TREPPENEIGNUNG
TRAPPENGESCHIKTHEID

PILE MATERIAL 100% PA 6 IMPREL®
COMPOSITION DU VELOURS
POLMATERIAAL
POOLMATERIAAL

PERMANENTLY ANTISTATIC ISO 6356
ANTISTATIQUE PERMANENT < 2 kV
PERMANENT ANTISTATISCH
PERMANENT ANTISTATISCH

PRIMARY BACKING Woven PP
SUPPORT PP tissé
TRÄGERMATERIAAL Bändchengewebe PP
TUFTDOEK Geweven PP

IMPACT NOISE RATING ISO 140-8
ISOLATION PHONIQUE 25 dB ΔLw
TRITTSCHALLVERBESSERUNG
GELUIDSISOLATIE

SECONDARY BACKING Action Back
DOSSIER
RÜCKEN
TAPIJTRUG

SOUND ABSORPTION ISO 354
ABSORPTION PHONIQUE 0,15 αw
SCHALLABSORPTIONSGRAD
GELUIDSABSORPTIE

PILE WEIGHT Ca. 730 gr/m²
POIDS DU VELOURS
POLEINSATZGEWICHT
POOLGEWICHT

THERMAL RESISTANCE ISO 8302
RÉSISTANCE THERMIQUE 0,07 m² K/W
WÄRMEDURCHLASSWIDERSTAND
WARMTEDOORLAATWEERSTAND

TOTAL WEIGHT Ca. 1.660 gr/m²
POIDS TOTAL
GESAMTGEWICHT
TOTAAL GEWICHT

FASTNESS TO LIGHT ISO 105-B02
SOLIDITÉ A LA LUMIÈRE ≥ 5-6
LICHTECHTHEID
LICHTECHTHEID

PILE HEIGHT Ca. 4 mm
EPAISSEUR DU VELOURS
POLHÖHE
POOLHOOGTE

COLOUR FASTNESS TO WATER EN ISO 105-E01
SOLIDITÉ À L'EAU ≥ 4-5
WASSERECHTHEID
WATERECHTHEID

TOTAL HEIGHT Ca. 6,5 mm
EPAISSEUR TOTALE
GESAMTHÖHE
TOTALE DIKTE

FIRE RESISTANCE EN 13501-1
COMPORTEMENT AU FEU Cfl-s1 (if glued)
BRENNVERHALTEN
BRANDGEDRAG

TUFT DENSITY Ca. 225.000/m²
NOMBRES DE POINTS
NOPPENZAHL
AANTAL PUNTEN

RUBBING FASTNESS EN ISO 105-X12
SOLIDITÉ AU FROTTEMENT ≥ 4
REIBECHTHEID
WRIJFECHTHEID

PILE DENSITY Ca. 0,113 g/cm³
DENSITÉ DU VELOURS
POLROHDICHTHEID
POOLDICHTHEID

NUMBER OF COLOURS 14
NOMBRES DE COULEURS
ANZAHL FARBEN
AANTAL KLEUREN



CLASSIFICATION EN 1307
CLASSEMENT 32 - LC2
KLASSIFIKATION
CLASSIFICATIE

WIDTH EN ISO 3018
LARGEUR ca. 400 cm
BREITE some colours in ca. 500 cm
BREEDTE

UPEC U3 P3 E1 C0
 Certification CSTB:09/261

CASTOR CHAIR SUITABILITY EN 985
CHAISE À ROULETTES A: intensive use
STUHLROLLENEIGNUNG
ROLSTOELGESCHIKTHEID



EN14041

 14
 ITC CO BV
 Kanegemstraat 15 - BE 8700 Tielt
DOP: 1011#IE0ACV
 Textile Floor Covering EN1307
 Notified body 2401

 my.itc-carpets.com




moquettes touffetées et tissées en lés
<http://evaluation.cstb.fr>



Fortesse SDE NEW AB

The Long Play collection




▲ 138 4+5 m



▲ 40 4 m




▲ 144 4 & 5 m



▲ 12 4 & 5 m



▲ 197 4 & 5 m




▲ 96 4 & 5 m




▲ 90 4 & 5 m




▲ 39 4 m




▲ 64 4 m




▲ 299 4 m




▲ 177 4 & 5 m



▲ 174 4 m



▲ 173 4 & 5 m



▲ 24 4 m