



# AKTUA UX

## BOUTIQUE COLLECTION

<b>CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR</b>	Tufting 5/64" cut pile print Tufté 5/64" cut pile print Getuftet 5/64" cut pile print Getuft 5/64" cut pile print	<b>FASTNESS TO LIGHT SOLIDITÉ A LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID</b>	EN ISO 105-B02 ≥ 5-6
<b>PILE MATERIAL COMPOSITION DU VELOURS POLMATERIAL POOLMATERIAAL</b>	100% PA	<b>COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID</b>	EN ISO 105-E01 ≥ 4-5
<b>SECONDARY BACKING DOSSIER RÜCKEN TAPIJTRUG</b>	Ultratex® back	<b>FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG</b>	EN 13501-1 C <sub>FL</sub> -S1
<b>PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT</b>	± 435 gr/m <sup>2</sup>	<b>WIDTH LARGEUR BREITE BREEDTE</b>	EN ISO 3018 ca. 400, 500 cm
<b>TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT</b>	± 1.590 gr/m <sup>2</sup>	<b>DESIGN REPEAT CM RACCORD CM RAPPORT CM DESSINRAPPORT CM</b>	ca. 5,1(W) x 5,1(H)
<b>PILE THICKNESS EPAISSEUR DU VELOURS POLDICKE POOLDIKTE</b>	± 3 mm		
<b>TOTAL THICKNESS EPAISSEUR TOTALE GESAMTDICKE TOTALE DIKTE</b>	± 7 mm		
<b>TUFT DENSITY NOMBRE DE POINTS NOPPENZAHL AANTAL PUNTEN</b>	± 268.800/m <sup>2</sup>		
<b>PRODIS / GUT</b>	EF888CA3		
<b>CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE</b>	EN 1307 31 - LC1		0,13



ITC CO BV  
Kanegemstraat 15, B-8700 Tielt  
itc-carpets.com

EN 14041 <b>CE</b>
17
ITC CO BV Kanegemstraat 15 - BE 8700 Tielt
DOP: 1011#IE00CL Textile Floor Covering EN1307 Notified Body 2401

myitc-carpets.com